## Bill of Quantity (Sample) COMMERCIAL KITCHEN, WET AREA & CHEMICAL AREA AT FACTORY



ITEM	DESCRIPTIONS	UNIT	QTY	RATE (RM)	AMOUNT (RM)
	BQ Specification For Installation for Commercial Kitchen , Wet Area Chemical Area at Factory				
A	Wall Prepare and apply two coats of Davco K11 Slurry 613 Cementitious Waterproof at the rate of 2.0kg/m² all done in accordance to the manufacture's instructions.  25mm thick Davco Cement / Sand Mortar 123 incorporate with Davco Mortar Admix RL 4516 as described paving wood float to wall.  Fix tiles with Davco Super TTB 998 Cement Based Adhesive mix with Davco Davelastic 98 Latex Additive Jointing and pointing with Davcopoxy 271 Epoxy				
В	Floor Prepare and apply two coats of Davco K11 Slurry 613 Cementitious Waterproof at the rate of 2.0kg/m²				
	all done in accordance to the manufacture's instructions  25mm thick Davco Cement / Sand Mortar 123 incorporate with Davco Mortar Admix RL 4516 as described paving wood float to floor.				
	Fix tiles with Davco Super TTB 998 Cement Based Adhesive mix with Davco Davelastic 98 Latex Additive				
	Jointing and pointing with Davcopoxy 271 Epoxy Grout				
C	Skirting				
D	Riser				
E	Ditto				







16





